Part Number: XK4MDW62


18.4mm LED CLUSTER

Features

- •NO. OF BUILT-IN 5mm LED LAMPS: RED 4PCS.
- •WATERPROOF PACKAGE WITH HOOD SUITABLE FOR OUTDOOR AND INDOOR INFORMATION BOARDS.
- •CAN PRODUCE ANY COLOR IN VISIBLE SPECTRUM, INCLUDING WHITE LIGHT.
- •Rohs Compliant.







Notes:

- 1. All dimensions are in millimeters (inches).
- 2. Tolerance is \pm 0.25(0.01") unless otherwise noted.
- 3. Specifications are subject to change without notice.

Published Date : JAN 25,2008 Drawing No :XDSA1692 V5 Checked : B.L.LIU P.1/3



Part Number: XK4MDW62

18.4mm LED CLUSTER

Electrical / Optical Characteristics at TA=25 $^{\circ}$ C

| Symbol | Parameter | Device | Min | Тур. | Max. | Units | Test Conditions |
|--------|--|----------|------|------|------|-------|------------------------|
| Iv | Luminous Intensity | XK4MDW62 | 6700 | 9190 | - | mcd | IF=40mA |
| 2 01/2 | Viewing Angle | | - | 20 | - | deg | - |
| VF | Forward Voltage | | - | 3.8 | 5.0 | V | IF=40mA |
| λΡ | Wavelength of Peak Emission | | - | 640 | - | nm | IF=40mA |
| λ D | Wavelength of Dominant Emission | | - | 628 | - | nm | IF=40mA |
| Δλ 1/2 | Spectral Line Full Width At Half- Maximum | | - | 27 | - | nm | IF=40mA |
| IR | Reverse Current | | - | - | 20 | uA | $V_R = 5V$ |

Absolute Maximum Ratings at TA=25 $^{\circ}$ C

| Parameter | Туре | Units | | | |
|-----------------------|----------------|-------|--|--|--|
| Power dissipation | 300 | mW | | | |
| DC Forward Current | 60 | mA | | | |
| Reverse Voltage | 5 | V | | | |
| Operating Temperature | -40°C To +70°C | | | | |
| Storage Temperature | -40°C To +85°C | | | | |

Published Date : JAN 25,2008 Drawing No :XDSA1692 V5 Checked : B.L.LIU P.2/3




Part Number: XK4MDW62


18.4mm LED CLUSTER

PACKING & LABEL SPECIFICATIONS

XK4MDW62



1PCS/BAG



200PCS / BOX

25PCS / BOX



P/NO:XK4xxx

QTY: 1pcs

CODE: XXX

S/N : XX

LOT NO:



RoHS Compliant

Published Date : JAN 25,2008 Drawing No :XDSA1692 V5 Checked : B.L.LIU P.3/3