

PRELIMINARY SPEC


Features

- BUILT-IN CURRENT LIMITING RESISTOR FOR DIRECT APPLICATION OF DIFFERENT ACROSS CURRENT.
- LONG LIFE.
- LOW CURRENT, POWER SAVINGS.
- LOW MAINTENANCE.
- SOLID STATE, HIGH VIBRATION RESISTANT.
- 6V INTERNAL RESISTOR.
- RoHS COMPLIANT.



Notes:


1. All dimensions are in millimeters (inches).
2. Tolerance is $\pm 0.25(0.01)$ " unless otherwise noted.
3. Specifications are subject to change without notice







Absolute maximum ratings ($T_A=25^\circ\text{C}$)		SG (InGaAlP)	Unit
Reverse Voltage	V_R	5	V
Forward Voltage	V_F	7	V
Power Dissipation	P_T	231	mW
Operating Temperature	T_A	-40 ~ +70	°C
Storage Temperature	T_{stg}	-40 ~ +85	

Operating Characteristics ($T_A=25^\circ\text{C}$)		SG (InGaAlP)	Unit
Forward Current (Typ.) ($V_F=6\text{V}$)	I_F	20	mA
Forward Current (Max.) ($V_F=6\text{V}$)	I_F	33	mA
Reverse Current (Max.) ($V_R=5\text{V}$)	I_R	10	μA
Wavelength Of Peak Emission (Typ.) ($V_F=6\text{V}$)	λ_P	574	nm
Wavelength Of Dominant Emission (Typ.) ($V_F=6\text{V}$)	λ_D	568	nm
Spectral Line Full Width At Half-Maximum (Typ.) ($V_F=6\text{V}$)	$\Delta\lambda$	26	nm

Part Number	Emitting Color	Emitting Material	Lens-color	Luminous Intensity ($V=6\text{V}$) mcd		Wavelength nm λ_P	Viewing Angle 2 θ 1/2
				min.	typ.		
XYSG102W6V	Green	InGaAlP	Water Clear	380	895	574	40°
Published Date : JAN 15,2008 Drawing No : XDSA2977 V5 Checked : B.L.LIU P.1/3							





❖ SG




PACKING & LABEL SPECIFICATIONS


XYSG102W6V



100PCS/BAG




OUTSIDE LABEL



4K/BOX

2K/BOX



P/NO : XYxxx102x

QTY : 100 pcs CODE: XXX

S/N : XX

LOT NO :



XXXXXXXXXXXXXXXXXXXXXXXXXX

RoHS Compliant